

AMENDMENT TO THE SPECIFICATION

Please amend paragraph [0019] in the publication as follows:

Referring to both FIGS. 2-1 and 2-2, cable 224 includes a main electrical ~~connector~~ conductor 221, a first electrical ~~connector-conductor~~ 229 and a second electrical ~~connector~~ conductor 235. Those skilled in the art will recognized that multiple electrical ~~connectors~~ conductors can be housed in cable 224 to electrically connect to a clamp, such as clamp 200.

Please amend paragraph [0020] in the publication as follows:

The main electrical ~~connector-conductor~~ 221 is capable of carrying a high current such that the high current can charge a battery. Terminal 218 is electrically coupled to the main electrical ~~connector~~ conductor. Terminal 218 includes terminal hole 220 which aligns with first hole (not shown in FIGS. 2-1 or 2-2) of first hand grip 210. Removable fastener 222 (shown fastened in FIG. 2-1 and shown unfastened in FIG. 2-2) couples terminal 218 to first hand grip 210 through the first hole and terminal hole 220 such that fastener 222 can disconnect clamp 200 from cable 224.

Please amend paragraph [0021] in the publication as follows:

~~First electrical conductor 229 includes first portion 230 and second portion 232. Second electrical conductor 235 includes first portion 231 and second portion 233. First portion~~ Clamp 200 includes a first wire connector 230 of first electrical conductor 229 that is electrically coupled to conductive piece 236 at one end and coupled to a first electrical plug 226 at the other end. Clamp 200 also includes a second wire connector ~~First portion 231 of second electrical conductor 235 that~~ is electrically coupled to second jaw 208 through rivet 234 at one end and coupled to first electrical plug 226 at the other end. ~~Second portions 232 and 233 are coupled to cable 224 at one end and coupled to second electrical plug 228 at the other end. First and second electrical~~

| conductors 229 and 235 of cable 224 are electrically coupled to a second electrical plug 228.

First electrical plug 226 is removably electrically connected with second electrical plug 228.